

REV	DESCRIPTION	DESIGN	DATE
A0	Release	吴丹平	2016.06.27

Circuits	Dimensions (mm)			Circuits	Dimensions (mm)		
	DIM. A	DIM. B	DIM. C		DIM. A	DIM. B	DIM. C
02	2.50	5.60	8.00	08	17.50	20.60	23.00
03	5.00	8.10	10.50	09	20.00	23.10	25.50
04	7.50	10.60	13.00	10	22.50	25.60	28.00
05	10.00	13.10	15.50	11	25.00	28.10	30.50
06	12.50	15.60	18.00	12	27.50	30.60	33.00
07	15.00	18.10	20.50				

**主要技术参数 Main Specifications**

线数 (Poles): 02 to 12P  
 接触电阻 (Contact resistance):  $\leq 20m\Omega$   
 绝缘电阻 (Insulation resistance):  $\geq 500M\Omega$   
 额定电压 (Rated voltage): 250 V AC DC  
 额定电流 (Rated current): 3.0A AC DC  
 耐电压 (Withstand Voltage): 1500V AC/minute  
 温度范围 (Temperature Range):  $-25^{\circ}C \sim +85^{\circ}C$

**ORDER INFORMATION:**

C2501R-\*\*-\*\*\*-P

PART No. _____ No. OF CIRCUITS: 02~12	PACKAGING: P=PE PLASTIC MATERIAL: A5W=PA66 (White) A5K=PA66 (Black)
--	---

C							
B							
A	PEDESTAL		1 PCS	PA66			
ITEM	COMPONENT		Q'TY	MATERIAL			FINISH

<b>JKUN 温州健坤接插件有限公司</b> WENZHOU JKUN CONNECTOR CO.,LTD.			TITLE: -	
X.±0.5	X.±5'	USE:	PART NO.: C2501R-**-***-P	
.X±0.3	.X±2'	CUSTOMER		
.XX±0.25	.XX±1'	APPD:	DWG NO.: JKUN/GCCP-0597	
--	--	邵敬和		
		CHKD:	SCALE 1 : 1	
		田峰		
		DR:	SHEET 1 / 1	
		吴丹平		
UNITS: mm				

